

Alfaspir N



Very flexible pvc hose smooth on the inside, to used as a protection hose for cables, but also suitable for ventilation.

Construction: Grey self-extinguishing pvc with an embedded white hard pvc spiral. (anti shock)

Temperature: -5°C to +60°C

Applications

Ventilation, draining without pressure, suction of non-abrasives materials

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Vacuum (mH2O)	Coil length (m)
EOG020	20	0,75	125	30	5	50
EOG025	25	0,75	150	30	5	50
EOG030	30	0,8	190	40	5	50
EOG032	32	0,8	205	40	4,5	50
EOG035	35	0,8	235	45	4,5	50
EOG038	38	0,8	255	45	4,5	50
EOG040	40	0,85	290	50	4	50
EOG045	45	0,85	360	60	4	50
EOG050	50	0,85	440	60	4	50
EOG055	55	0,85	550	65	4	50
EOG060	60	0,85	500	70	4	50
EOG063	63	0,9	535	75	4	50
EOG070	70	0,9	590	85	4	50
EOG075	75	0,9	640	95	4	50
EOG080	80	0,95	740	115	4	50
EOG090	90	0,95	850	130	4	50
EOG100	100	1	970	140	4	30
EOG110	110	1	1050	150	4	30
EOG120	120	1	1150	160	4	30
EOG125	125	1	1240	165	4	30
EOG130	130	1,1	1650	170	3,5	30
EOG140	140	1,1	1440	180	3,5	30
EOG150	150	1,1	1700	180	3,5	20
EOG160	160	1,15	1900	200	3,5	20
EOG170	170	1,15	2350	245	3	20
EOG180	180	1,15	2200	290	3	20
EOG200	200	1,2	2600	380	2,5	20
EOG250	250	1,2	3600	470	2,5	10
EOG300	300	1,3	4500	560	2,5	10