


AX SAND 10 bar



Antistatic NR/SBR rubber hose for delivery of wet and dry abrasive media. Normally used in sand blasting service and for surface treatment.

Temperature: -40°C to +70°C

- **Tube:** smooth black NR/SBR
- **Reinforcement:** textile yarn
- **Cover:** black, abrasion and weather resistant NR/SBR rubber with cloth impression,

Abrasion loss of tube: rubber compound according to DIN 53516: 70+/-5mm³

Remark: also available on request with working pressure 12 or 18 bar

Applications

sand, concrete, woodchips, ...

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Coil length (m)
TBD013	13 x 25	440	10	30	40 - 61
TBD019	19 x 33	660	10	30	40 - 61
TBD025	25 x 40	880	10	30	40 - 61
TBD032	32 x 48	1.160	10	30	40 - 61
TBD038	38 x 54	1.330	10	30	40 - 61
TBD040	40 x 60	1.830	10	30	40 - 61
TBD050	51 x 71	2.200	10	30	40 - 61
TBD060	60 x 80	2.530	10	30	40 - 61
TBD065	65 x 85	2.700	10	30	40 - 61
TBD075	75 x 95	4.020	10	30	40 - 61
TBD080	80 x 105	4.180	10	30	40 - 61
TBD090	90 x 115	4.630	10	30	40 - 61
TBD100	102 x 127	5.170	10	30	40 - 61

Product ID: 40135

Source URL: <http://alfaflex.be/en/products/40000/40100/ax-sand-10-bar-0>