

Coupler C



Female part or coupler with serrated hose shank.
Perfect for assembly with clamps or binding.

Norm coupling: Fed Mil A-A-59326A

Alloys: Aluminium, Stainless Steel,
Polypropylene, Brass

Seals: NBR (std), PTFE, Viton, Hypalon or EPDM

ND (mm)	Diameter (inch)	For hose (mm)	Ref Alu	Ref SS	Ref Brass	Ref PP
15	1/2"	13	KEAC013	KESC013	KEMC013	KEEC013
20	3/4"	19	KEAC019	KESC019	KEMC019	KEEC019
25	1"	25	KEAC025	KESC025	KEMC025	KEEC025
32	1" 1/4	2	KEAC030	KESC030	KEMC030	KEEC030
40	1" 1/2	38	KEAC040	KESC040	KEMC040	KEEC040
50	2"	50	KEAC050	KESC050	KEMC050	KEEC050
65	2" 1/2	63	KEAC065	KESC065	KEMC065	-
80	3"	75	KEAC080	KESC080	KEMC080	KEEC080
100	4"	100	KEAC100	KESC100	KEMC100	KEEC100
125	5"	125	KEAC125	KESC125	KEMC125	-
150	6"	150	KEAC150	KESC150	KEMC150	-

Product ID: 90330

Source URL: <http://alfaflex.be/en/products/90000/90001/90300/kamlock-coupler-c-0>