

Storz male threaded



Storz half-coupling with male thread. Available with fixed head or swivel.

Lug distances(1): D = 31 , C = 66 , B = 89 , A = 133

Thread: BSP, DIN ISO 228

Alloys: aluminium or Stainless Steel(2).

Profiled seal: NBR

Working pressure: 16 bar (ND205: 10bar)

(1) Most common, other available (see table)

(2) Please contact us

ND	Inch	Lug dist. (mm)	DIN	Ref	Ref Swivel
25	1"	31		SZM031025	
32	1"	44		SZM044025	
32	1" 1/4	44		SZM044032	
38	1" 1/2	51		SZM051038	
38	2"	51		SZM051052	
52	1"	66		SZM066025	
52	1" 1/4	66		SZM066032	
52	1" 1/2	66		SZM066038	
52	2"	66		SZM066052	SZMD066052
52	2" 1/2	66		SZM066065	
65	2"	81		SZM081052	
65	2" 1/2	81		SZM081065	SZMD081065
65	3"	81		SZM081075	
75	2"	89		SZM089052	
75	2" 1/2	89		SZM089065	SZMD089065
75	3"	89		SZM089075	SZMD089075
100	4"	115		SZM115100	
110	4"	133		SZM133100	SZMD133100
150	5"	160		SZM160125	SZMD160125
165	6"	188		SZM188150	
205	8"	220		SZM220200	

Product ID: 90830

Source URL: <http://alfaflex.be/en/products/90000/90001/90800/storz-met-manndraad-0>