

ASFA-S

ASFA-S worm-drive clips have a smooth band underside and beveled band edges to assure the hose doesn't get damaged while or after mounting.

Following DIN 3017 and available in W2 and W4
Bandwidth: 12mm

W2: zinc-plated screw with stainless steel (AISI-430) band and housing

W4: screw, band and housing in stainless steel (AISI-304)

Applications

W2: automotive applications, in agriculture, and in fluid transfer applications

W4: industrial applications where there is a high corrosion resistance required.

Ø min - max (mm)	Max torque (Nm)	Box qty (pc)	Ref W2	Ref W4
16 - 27	4,2	50	KASH016	-
20 - 32	5,2	50	KASH020	KASHI020
25 - 40	5,2	50	KASH025	KASHI025
32 - 50	6,0	50	KASH032	KASHI032
40 - 60	6,0	50	KASH040	KASHI040
50 - 70	6,8	50	KASH050	KASHI050
60 - 80	6,8	50	KASH060	KASHI060
70 - 90	6,8	50	KASH070	KASHI070
80 - 100	6,8	25	KASH080	KASHI080
90 - 110	6,8	25	KASH090	KASHI090
100 - 120	6,8	25	KASH100	KASHI100
110 - 130	6,8	25	KASH110	KASHI110
120 - 140	6,8	25	KASH120	KASHI120
130 - 150	6,8	25	KASH130	KASHI130
140 - 160	6,8	25	KASH140	KASHI140
150 - 170	6,8	25	KASH150	KASHI150
160 - 180	6,8	25	KASH160	-
170 - 190	6,8	10	KASH170	KASHI170
190 - 210	6,8	10	KASH190	KASHI190
200 - 220	6,8	10	KASH200	-
210 - 230	6,8	10	-	KASHI210
220 - 240	6,8	10	KASH220	KASHI220

Product ID: 122020

Source URL: <http://alfaflex.be/en/products/120000/asfa-s-0>