

SBR



SBR rubber sheets with or without ply are very suitable for divers applications with the exception of chemicals and hydrocarbons. Both surfaces are smooth.

Temperature: -10°C to +70°C

- Hardness : 65 °Shore +/-5
- Density: 1,6 g/cm³
- Tensile strength : 3 MPa
- Elasticity at rupture: 200 %

Thickness (mm)	Width (m)	Length (m)	Ref no ply	Ref 1 ply	Ref 2 ply
1	1,40	10,00	RP0100	-	-
1,5	1,40	10,00	RP01500	-	-
2	1,40	10,00	RP0200	RP0201	-
3	1,40	10,00	RP0300	RP0301	RP0302
4	1,40	10,00	RP0400	RP0401	RP0402
5	1,40	10,00	RP0500	RP0501	RP0502
6	1,40	10,00	RP0600	RP0601	RP0602
8	1,40	5,00	RP0800	RP0801	RP0802
10	1,40	5,00	RP1000	RP1001	RP1002
15	1,40	5,00	RP1500	-	RP1502
20	1,00	1,00	RP2000	-	-
30	1,00	1,00	RP3000	-	-
40	1,00	1,00	RP4000	-	-
50	1,00	1,00	RP5000	-	-

Product ID: 31010

Source URL: <https://alfaflex.be/en/products/30000/31000/sbr-0>