




Alfaflex ATH



Professional waterhose for supplying or spraying water in both home and industry.

Temperature: -25°C to +60°C

- **Tube:** smooth and pure pvc
- **Intermediate layer:** 100% recycled black pvc
- **ATH layer:** special anti torsion insertion to reduce torsion under pressure, polyester fibre
- **Cover:** yellow uv proof flexible pvc

No barium, nor cadmium or lead

Test Pressure: 25 bar

Warranty: 12 year

Applications

Water hose for various means of water supply and irrigation, domestic or industrial

Reference	Diameter (mm)	Weight (g/m)	Working Pressure (bar)	Coil length (m)
AF12	12,5 x 17,5	150	12	25 - 50 - 100
AF15	15 x 20,5	192	12	15 - 25 - 50 - 100
AF19	19 x 25,5	270	12	25 - 50 - 100
AF25	25 x 32,5	420	8	25 - 50 - 100
AF30	30 x 39	600	8	25 - 50 - 100
AF32	32 x 42	715	8	25 - 50 - 100
AF35	35 x 45	751	8	25 - 50 - 100
AF38	38 x 48	860	8	25 - 50 - 100
AF40	40 x 51	930	8	25 - 50 - 100
AF50	50 x 63	1390	8	25 - 50

Product ID: 11010

Source URL: <https://alfaflex.be/en/products/10000/11000/alfaflex-ath-0>