



## Fuelflex 10 bar



Very flexible PVC hose, especially for hydrocarbons and derivatives  
Reinforced by durable textile thread

Temperature: -15°C to +60°C

The Fuelflex is a reinforced pvc hose for conveying hydrocarbons and derivatives up to 10 bar.

**Tube:** transparent pvc, resistant to hydrocarbons (> Ø20mm black)

**Reinforcement:** high tensile thread

**Cover:** transparent blue pvc, resistant to hydrocarbons (> Ø20mm black)

**ATTENTION:** not for gasoline

### Applications

pumps, heaters, ...

| Reference | Diameter (mm) | Bending radius (mm) | Weight (g/m) | Working Pressure (bar) | Burst Pressure (bar) | Coil length (m) |
|-----------|---------------|---------------------|--------------|------------------------|----------------------|-----------------|
| TFU06     | 6,3 x 11      | 80                  | 50           | 10                     | 40                   | 50              |
| TFU08     | 8 x 14        | 128                 | 60           | 10                     | 40                   | 25 - 50         |
| TFU10     | 10 x 16       | 149                 | 80           | 10                     | 33                   | 50              |
| TFU12     | 12 x 19       | 210                 | 100          | 10                     | 33                   | 50              |
| TFU15     | 15 x 23       | 295                 | 125          | 10                     | 33                   | 50              |
| TFU20     | 20 x 28       | 370                 | 150          | 10                     | 30                   | 25 - 50         |
| TFU25     | 25 x 32,5     | 425                 | 170          | 8                      | 24                   | 25 - 50         |
| TFU30     | 30 x 39       | 598                 | 200          | 8                      | 24                   | 25 - 50         |

Product ID: 12190

Source URL: <https://alfaflex.be/en/products/10000/12000/fuelflex-10-bar-0>