

# Azur



Flexible pvc spiral hose, for both domestic as professional use. Can be connected on both suction and delivery side of a pump.

Temperature: -10°C to +60°C

**Construction:** transparent plasticized pvc, reinforced by a blue hard pvc spira with a smooth inner tube

Security coefficient at 20°C: 3 times the WP

## Applications

Suction and delivery in agricultural industry, sump pumps

## Assembly

all types of couplings, assembled with hose clamps

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Vacuum (mH20)	Coil length (m)
SA013	13	2,5	110	60	4	6	50
SA016	16	2,5	180	80	4	6	50
SA020	20	2,4	210	110	4	6	50
SA025	25	2,4	270	140	4	6	50
SA030	30	2,5	330	160	4	6	50
SA032	32	2,6	360	175	4	6	50
SA035	35	2,6	420	200	4	6	50
SA038	38	3,0	470	210	4	6	50
SA040	40	3,0	510	220	4	6	50
SA045	45	3,2	585	245	4	6	50
SA050	50	3,6	710	275	4	6	50
SA055	55	3,6	760	310	4	6	50
SA060	60	3,6	860	240	4	6	50
SA063	63	3,7	910	360	4	6	50
SA070	70	3,9	1060	460	3	6	50
SA075	75	4,1	1150	500	3	6	50
SA080	80	4,5	1360	540	3	5	50
SA090	90	4,8	1620	580	2	5	25 - 50
SA100	100	5,4	1950	620	2	5	25 - 50
SA110	110	5,6	2530	640	2	5	30
SA125	125	6,2	4200	750	2	5	30
SA150	150						30



**Source URL:** <https://alfaflex.be/en/products/10000/14000/azur-0>