

Aquastar



Flexible and elastic pvc hose, especially developed for the installation in pools, jacuzzi's, spa's, ...

Temperature: -10°C to +60°C

These hoses are calibrated on the outer diameter and have a smooth outside for easy glueing on the typical pvc fittings with the usual glues.

Construction: plasticized blue, grey or white pvc, reinforced by a concealed hard white pvc spiral, in- and the outside of the hose are smooth

Hardness: 72°ShA

Working pressure (WP) at 23°C

Safety coefficient at 20°C: 3 times MP

Each roll is tested on watertightness

Ext.Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Ref Blue	Ref Grey	Ref White	Coil length (m)
20	2,5	170	140	6	AQB20	AQG20	AQW20	25 - 50
25	3	250	160	6	AQB25	AQG25	AQW25	25 - 50
32	3,5	420	200	6	AQB32	AQG32	AQW32	25 - 50
40	4	520	200	5	AQB40	AQG40	AQW40	25 - 50
50	4	750	200	5	AQB50	AQG50	AQW50	25 - 50
63	4	960	250	5	AQB63	AQG63	AQW63	25 - 50
75	5	1.370	280	4	AQB75	AQG75	AQW75	25 - 50

Product ID: 14100

Source URL: <https://alfaflex.be/en/products/10000/14000/aquastar-0>