

Alfavac PU H



Very flexible and extremely durable polyurethane (PU) hose, that can be used to transport abrasive materials by air and that has a good resistance to hydrolysis and bacteria. Doesn't rip easily and can be earthed by connecting both ends of the steel helix.

Temperature: -30°C to +100°C

Construction: transparent PU with an embedded steel helix with white PVC cover.

Remark: Heavy version

Applications

woodchips, grains, sawdust,... in the food, forestry, wood,... industry

Reference	Diameter (mm)	Wall thickness (mm)	Wire (mm)	Weight (g/m)	Bending radius (mm)	Vacuum (mH20)	Coil length (m)
VFPUH050	50	1,3	1,9	650	150	3	10
VFPUH060	60	1,3	1,9	660	180	3	10
VFPUH065	65	1,4	2,2	680	200	3	10
VFPUH075	75	1,4	2,2	840	220	3	10
VFPUH080	80	1,4	2,2	890	240	2	10
VFPUH090	90	1,4	2,2	1.000	270	2	10
VFPUH100	100	1,4	2,7	1.220	300	2	10
VFPUH110	110	1,4	2,7	1.240	330	2	10
VFPUH120	120	1,5	2,7	1.290	300	2	10
VFPUH125	125	1,5	2,7	1.350	320	2	10
VFPUH140	140	1,5	2,7	1.525	400	1	10
VFPUH150	150	1,5	2,7	1.600	425	1	10
VFPUH160	160	1,5	2,7	1.690	450	1	10
VFPUH180	180	1,5	2,7	1.890	520	1	10
VFPUH200	200	1,5	2,7	2.010	600	1	10
VFPUH250	250	1,5	3,5	3.520	750	1	10
VFPUH300	300	1,5	3,5	4.080	900	1	10
VFPUH350	350	1,5	3,5	4.950	1.100	1	10
VFPUH400	400	1,5	3,5	5.670	1.200	0,5	10
VFPUH500	500	1,5	3,5	7.040	1.500	0,5	10

Product ID: 14200

Source URL: <https://alfaflex.be/en/products/10000/14000/alfavac-pu-h-0>