

## NBR (nitril)



NBR rubber sheets with or without ply are suitable for applications where contact with oils or lubricants are possible, however with poor resistance to aging and heat. Two smooth surfaces.

Temperature: -20°C to +70°C

- Hardness : 65 °Shore +/-5
- Density: 1,5 g/cm<sup>3</sup>
- Tensile strength : 4 Mpa
- Elasticity at rupture: 250 %

### Applications

petrochemicals, workshops, ...

Thickness (mm)	Width (m)	Length (m)	Ref no ply	Ref 1 ply	Ref 2 ply
1	1,40	10	RPNBR0100	-	-
2	1,40	10	RPNBR0200	RPNBR0201	-
3	1,40	10	RPNBR0300	RPNBR0301	-
4	1,40	10	RPNBR0400	RPNBR0401	RPNBR0402
5	1,40	10	RPNBR0500	RPNBR0501	RPNBR0502
6	1,40	10	RPNBR0600	RPNBR0601	RPNBR0602
8	1,40	5	RPNBR0800	RPNBR0801	RPNBR0802
10	1,40	5	RPNBR1000	RPNBR1001	RPNBR1002
15	1,40	5	RPNBR1500	-	-

Product ID: 31020

Source URL: <https://alfaflex.be/en/products/30000/31000/nbr-nitril-0>