

## AX Dry Cement



Antistatic NR/SBR delivery hose for conveying and handling dry abrasive bulk materials at low pressure (10 bar).

Temperature: -40°C to +70°C

- **Tube:** black smooth anti static NR/SBR rubber
- **Reinforcement:** high tenacity textile yarn
- **Cover:** black antistatic NR/SBR rubber with cloth impression, abrasion and weathering resistant

**Abrasion loss of the tube:** rubber compound according to DIN 53516 70±5 mm<sup>3</sup>

**Remark:** Other diameters, pressure ratings and inner tube rubber quality (higher abrasion resistance, light coloured para rubber) available on request.

### Applications

cement, sand, gravel, chalk, lime, ...

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Coil length (m)
TBDD050	51 x 65	1.740	10	30	40 - 61
TBDD075	76 x 92	2.250	10	30	40 - 61
TBDD090	90 x 110	3.680	6	18	40
TBDD100	102 x 118	3.180	10	30	40 - 61
TBDD110	110 x 129	3.950	8	24	40
TBDD115	115 x 135	4.300	8	24	40

Product ID: 40105

Source URL: <https://alfaflex.be/en/products/40000/40100/ax-dry-cement-0>