

## AX NBR S&D EN 12115



Mandrel built suction and delivery hose for conveying domestic oils and fuels. The maximum vacuum capacity of the hose is 80%.

Temperature: -30°C to +100°C

- **Inner tube:** smooth black NBR
- **Reinforcements:** high tensile textile inserts, steel helix and antistatic copper wire
- **Cover:** black smooth NBR with cloth finish, resistant to oil

**Norm:** EN12115

### Applications

tank trucks, petrol stations, ...

| Ref | Diameter (mm) | Weight (g/m) | WP (bar) | BP (bar) | Bending Radius (mm) | Ref |
|-----|---------------|--------------|----------|----------|---------------------|-----|
|     | 30 x 40       | 970          | 16       | 48       | 200                 |     |
|     | 40 x 50       | 1.790        | 16       | 48       | 250                 |     |
|     | 50 x 64       | 2.330        | 16       | 48       | 300                 |     |
|     | 60 x 74       | 2.710        | 16       | 48       | 360                 |     |
|     | 70 x 84       | 3.130        | 16       | 48       | 420                 |     |
|     | 75 x 89       | 3.330        | 16       | 48       | 500                 |     |
|     | 80 x 94       | 3.530        | 16       | 48       | 600                 |     |
|     | 100 x 116     | 4.940        | 12       | 36       | 1.000               |     |

Product ID: 40618

Source URL: <https://alfaflex.be/en/products/40000/40600/ax-nbr-sd-en-12115-0>