

Guillemin with serrated shank



Symmetrical half coupling with hose shank and locking ring.
Available in Aluminium, Stainless Steel, Brass or Polypropylene

Working Pressure: 16 bar

Standard with NBR seal

Remark: This type is always supplied with a locking ring

(ND = nominal diameter)

ND	Inch	For hose (mm)	Ref Alu	Ref SS	Ref Brass	Ref PP
20	1"	25	GUT025	GUIT025	GUBT025	-
25	1" 3/16	30	GUT030	GUIT030	GUBT030	-
30	1" 1/4	32	GUT032	-	-	-
30	1" 1/4	35	GUT035	GUIT035	GUBT035	-
40	1" 1/2	30	GUT040030	-	-	-
40	1" 1/2	35	GUT040035	-	-	-
40	1" 1/2	40	GUT040	GUIT040	GUBT040	GUPT040
40	1" 1/2	45	GUT045	GUIT045	GUBT045	GUPT045
50	2"	50	GUT050	GUIT050	GUBT050	GUPT050
50	2"	55	GUT055	GUIT055	GUBT055	GUPT055
65	2" 1/2	63	GUT065	GUIT065	GUBT065	-
65	2" 1/2	70	GUT070	GUIT070	GUBT070	-
80	3"	75	GUT075	GUIT075	GUBT075	GUPT075
80	3"	80	GUT080	GUIT080	GUBT080	-
80	3"	90	GUT090	GUIT090	GUBT090	GUPT090
100	4"	100	GUT100	GUIT100	GUBT100	-
100	4"	105	GUT105	-	-	-
100	4"	110	GUT110	GUIT110	GUBT110	GUPT110
150	6"	152	GUT150	-	-	-

Product ID: 90110

Source URL: <https://alfaflex.be/en/products/90000/90001/90100/guillemin-met-traptule-0>