

Storz male threaded



Storz half-coupling with male thread. Available with fixed head or swivel.

Lug distances(1): D = 31 , C = 66 , B = 89 , A = 133

Thread: BSP, DIN ISO 228

Alloys: aluminium or Stainless Steel(2).

Profiled seal: NBR

Working pressure: 16 bar (ND205: 10bar)

(1) Most common, other available (see table)

(2) Please contact us

| ND | Inch | Lug dist. (mm) | DIN | Ref | Ref Swivel |
|-----|--------|-------------------|-----|-----------|------------|
| 25 | 1" | 31 | | SZM031025 | |
| 32 | 1" | 44 | | SZM044025 | |
| 32 | 1" 1/4 | 44 | | SZM044032 | |
| 38 | 1" 1/2 | 51 | | SZM051038 | |
| 38 | 2" | 51 | | SZM051052 | |
| 52 | 1" | 66 | | SZM066025 | |
| 52 | 1" 1/4 | 66 | | SZM066032 | |
| 52 | 1" 1/2 | 66 | | SZM066038 | |
| 52 | 2" | 66 | | SZM066052 | SZMD066052 |
| 52 | 2" 1/2 | 66 | | SZM066065 | |
| 65 | 2" | 81 | | SZM081052 | |
| 65 | 2" 1/2 | 81 | | SZM081065 | SZMD081065 |
| 65 | 3" | 81 | | SZM081075 | |
| 75 | 2" | 89 | | SZM089052 | |
| 75 | 2" 1/2 | 89 | | SZM089065 | SZMD089065 |
| 75 | 3" | 89 | | SZM089075 | SZMD089075 |
| 100 | 4" | 115 | | SZM115100 | |
| 110 | 4" | 133 | | SZM133100 | SZMD133100 |
| 150 | 5" | 160 | | SZM160125 | SZMD160125 |
| 165 | 6" | 188 | | SZM188150 | |
| 205 | 8" | 220 | | SZM220200 | |

Product ID: 90830

Source URL: <https://alfaflex.be/en/products/90000/90001/90800/storz-met-manddraad-0>