

ASFA-L

ASFA-L worm-drive clips are very compact, but are also of outstanding quality. The smooth band underside and beveled band edges assure that the hose doesn't get damaged while or after mounting.

Following DIN 3017 and available in W2 and W4 version.
Bandwidth: 9mm

W2: zinc-plated screw with stainless steel (AISI-430) band and housing
W4: screw, band and housing in stainless steel (AISI-304)

Applications

W2: very suitable for standard domestic or professional applications
W4: suitable for standard applications with possible corrosion

Ø min - max (mm)	Max torque (Nm)	Box qty (pc)	Ref W2	Ref W4
8 - 16	3,0	200	KAS08	KASI08
12 - 22	3,0	200	KAS12	KASI12
16 - 27	3,5	200	KAS16	KASI16
20 - 32	3,5	200	KAS20	KASI20
25 - 40	4,0	100	KAS25	KASI25
30 - 45	4,0	100	KAS30	-
32 - 50	4,0	100	KAS32	KASI32
40 - 60	4,0	100	KAS40	KASI40
50 - 70	4,0	100	KAS50	-
60 - 80	4,0	100	KAS60	KASI60
70 - 90	4,0	50	KAS70	KASI70
80 - 100	4,0	50	KAS80	-

Product ID: 122010

Source URL: <https://alfaflex.be/en/products/120000/asfa-l-0>