


Panneaux



Qualité standard bleutée transparent

Dureté 75°ShA

Température: -20°C à +50°C

| Largueur x Ep (mm) | Poids (g/m) | Référence | Courronage (m) |
|-----------------------|----------------|-----------|-------------------|
| 1000 x 1 | 1250 | LC10001 | 20 |
| 1000 x 2 | 2500 | LC10002 | 20 |
| 1000 x 3 | 3750 | LC10003 | 20 |
| 1000 x 4 | 5000 | LC10004 | 20 |
| 1000 x 5 | 6250 | LC10005 | 20 |
| 1000 x 6 | 7500 | LC10006 | 20 |
| 1000 x 7 | 8750 | LC10007 | 20 |
| 1000 x 8 | 10000 | LC10008 | 20 |
| 1000 x 10 | 12500 | LC10010 | 20 |
| 1200 x 1 | 1500 | LC12001 | 20 |
| 1200 x 2 | 3000 | LC12002 | 20 |
| 1200 x 3 | 4500 | LC12003 | 20 |
| 1200 x 4 | 6000 | LC12004 | 20 |
| 1200 x 5 | 7500 | LC12005 | 20 |
| 1200 x 6 | 9000 | LC12006 | 20 |
| 1200 x 7 | 10500 | LC12007 | 20 |
| 1200 x 8 | 12000 | LC12008 | 20 |
| 1500 x 2 | 3750 | LC15002 | 20 |
| 1500 x 3 | 5630 | LC15003 | 20 |
| 1500 x 4 | 7500 | LC15004 | 20 |
| 1500 x 5 | 9380 | LC15005 | 20 |
| 1500 x 6 | 11250 | LC15006 | 20 |
| 1500 x 7 | 13130 | LC15007 | 20 |
| 1800 x 3 | 6750 | LC18003 | 20 |
| 1800 x 4 | 9000 | LC18004 | 20 |
| 1800 x 5 | 11250 | LC18005 | 20 |
| 2200 x 3 | 8250 | LC22003 | 20 |
| 2200 x 4 | 11000 | LC22004 | 20 |
| 2200 x 5 | 13750 | LC22005 | 20 |
| 2200 x 7 | 19250 | LC22007 | 20 |

Product ID: 22000

URL source: <https://alfaflex.be/fr/products/20000/platen-0>